

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705, dated April 19, 1899 - (DCSO records Vol. 1 Page(s) 272)

-----  
Set a Fir post 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S13 on W. face; from which

A Fir 8" dia., bears N.9°W., 10 lks. dist. mkd. ¼ S BT.

A Fir 6" dia., bears S.70°W., 19 lks. dist. mkd. ¼ S BT

The old ¼ sec. cor. bears S.87°E., 5 lks. dist.; I destroy it.

\* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM survey by Thomas A. Tillman; Robert L. Holm & Floyd A. Brooks, Cadastral Surveyors, under Group #307, surveyed May 1957/Sept. 1958 - (DCSO records Vol. 31 Page(s) 13034)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap mkd:

¼  
T 19 S  
S 13  
R 10 W  
1958

from which

A Cedar 33" dia., bears N.80¼°W., 67 lks., mkd. ¼ S13 BT.

A Fir 48" dia., bears S.70°W., 40 lks., mkd. ¼ S13 BT.

BLM Resurvey by Robert W. Dahl, Cadastral Surveyor, under Group #1450, surveyed Aug. 1988/Oct. 1989 - (DCSO records Vol. 49 Page(s) 18770)

-----  
The ¼ sec. cor. of sec. 13 only, monumented with an iron post 2½" dia., firmly set, projecting 1" above ground with brass cap mkd. in 1958,

from which the remains of bearing trees mkd. by Tillman, etal  
A Fir stump 50" dia., bears S.79½°W., 40 lks. dist., with healed blaze. (Rec. S.70°W.)

A Cedar snag 34" dia., 1 ft. high, bears N.80¼°W., 67 lks. dist., no marks visible.

and new bearing trees:

A Fir 7" dia., bears N.82¼°W., 97½ lks. dist., mkd. X BT.

A Fir 14" dia., bears N.41°W., 126½ lks., mkd. ¼ S13 BT.