

TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 100540

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 7 only

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

from which

A stainless steel post 28" long, 2½" dia., set 28" in the ground for a reference monument, bears N.29°23'E., 102.9 lks. dist., with brass cap mkd. RM ¼ S7 67.9 FT TO COR 1989 and an arrow pointing to the corner.

and a bearing tree mkd. by Tillman, Holm and Brooks:

A Fir 34" dia., bears N.44°E., 163 lks. dist. with healed blaze.

and a bearing tree mkd. by Baker in 1988:

A Hemlock 25" dia., bears S.68°E., 75 lks. dist. with scribe marks ¼ S7 BT visible on partially healed blaze. Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

From this same point, a point established as the ¼ sec. cor. by Baker in 1988, bears S.87°44'W., 0.177 chs. dist., monumented with an alum. post, 2½" dia., firmly set, projecting 6" above ground, with alum. cap mkd. T19S R9W R10W ¼ S7 S1978 1988. This point was established using improper control is is not utilized in this survey.

Removed alum. monument, set rebar. Position change. May 1990, C.S. File 63/104 - D. Baker

Cor. Fd. OK March 1997 by D. Baker - M 124-48