

TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 18 & 19

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 414)

Set a Fir post, 3 ft. long, 3" sq., 24" in the ground, for ¼ secs. cor. mkd: ¼ S8 on N and 19 on S faces; from which
 A Fir, 4" dia., bears N.70°E., 19 lks., mkd: ¼ S BT.
 A Fir, 5" dia., bears S.3°W., 21 lks., mkd: ¼ S BT.
Old cor. bears South 10 lks., I destroy it.
* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

Robert Ward, Jr. - For: Siuslaw Nat. Forest - June 1991 - M113-37 A&B

Set - USFS Alum. corner monument stamped "T19S R9W ¼ S18 S19 LS 1091 1991"
 19" Hemlock bears N.30°W., 24.0 ft., scribed: ¼ S18 BT"
 10" Hemlock bears N.36°E., 34.7 ft., scribed: ¼ S18 BT"
 8" Hemlock bears S.52°E., 27.8 ft., scribed: ¼ S19 BT"
 10" Hemlock bears S.46°W., 2.6 ft., scribed: ¼ S19 BT"