

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 413-14)

The cor. of sec. 17, 18, 19, & 20, established on former survey*, which is a post, 3 ft. long, 4" sq. set 24" in the ground, marked T19S S17 on NE, R9W S20 on SE, S19 on SW, and S18 on NW faces, with 3 notches on S & 5 notches on E edges; from which

- A Fir, 12" dia., bears N.46°E., 30 lks., mkd: T19S R9W S17 BT.
- A Fir, 12" dia., bears S.76½°E., 29 lks., mkd: T19S R9W S20 BT.
- A Fir, 7" dia., bears S.11°W., 51 lks., mkd: T19S R9W S19 BT.
- A Fir, 7" dia., bears N.17°W., 39 lks., mkd: T19S R9W S18 BT.

* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

Robert Ward, Jr. - For: Siuslaw Nat. Forest - June 1991 - M113-37 A&B

-
- Set - USFS Alum. corner monument stamped "T19S R9W S17 S18 S19 S20 L.S. 1091 1991"
- 9" Fir bears N.29°E., 22.1 ft. scribed "T19S R9W S17 BT"
 - 11" Fir bears N.13°W., 10.4 ft. scribed "T19S R9W S18 BT"
 - 10" Fir bears S.80°W., 5.5 ft. scribed "T19S R9W S19 BT"
 - 13" Fir bears S.23°E., 18.6 ft. scribed "T19S R9W S20 BT"