

TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 415)

Set a Fir post, 3 ft. long, 3" sq., 24" in the ground, for ¼ secs. cor. mkd: ¼ S17 on W and 18 on E faces; from which
 A Fir, 6" dia., bears N.60°W., 29 lks., mkd: ¼ S BT.
 A For, 5" dia., bears S.46°E., 10 lks., mkd: ¼ S BT.
Old cor. bears West 15 lks., I destroy it.
* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

Robert Ward, Jr. - For: Siuslaw Nat. Forest - June 1991 - M113-37 A&B

Set - USFS Alum. corner monument stamped "T19S R9W ¼ S17 S18 LS1091 1991"
 11" Fir bears S.56°E., 33.6 ft., scribed: ¼ S17 BT
 18" Fir bears S.77°W., 6.6 ft., scribed: ¼ S18 BT
 12" Fir bears N.31°W., 38.5 ft., scribed: ¼ S18 BT
 13" Fir bears N.32°E., 18.7 ft., scribed: ¼ S17 BT