

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 8, 17, & 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 415)

-----  
Set a sandstone, 16x10x6", 12" in the ground, for cor. of secs. 7, 8, 17, & 18, marked with 4 notches on S & 5 notches on E edge; from which

- A Fir, 6" dia., bears N.22°E., 4 lks., mkd: T19S R9W S8 BT.
- A Fir, 6" dia., bears S.49°E., 51 lks., mkd: T19S R9W S17 BT.
- A Hemlock, 15" dia., bears S.40°W., 33 lks., mkd: T19S R9W S18 BT.
- A Fir, 12" dia., bears N.75°W., 13 lks., mkd: T19S R9W S7 BT.

Old cor. bears S.25°W., 30 lks., I destroy it.

\* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM dependent resurvey by Thomas A. Tillman, Robert L. Holm, & Floyd A. Brooks, under Group # 307, Surveyed May 1957 thru Sept. 1958 - (DCSO records Vol. 31 Page(s) 13062)

-----  
The cor. of secs. 7, 8, 17, & 18, is monumented with a sandstone 16x10x6 ins., firmly set, 12" in the ground, with 4 notches on the S and 5 notches on the E edges, from which the orig. BTs:

- A decayed Fir stump, bears N.22°E., 4 lks.
- A Fir stump, 18" dia., bears S.49°E., 48 lks., with scribe marks T19S R9W S17 BT visible on opened blaze. (Rec. dist. 51 lks.)
- A Hemlock, 30" dia., bears S.40°W., 35 lks., with a healed blaze. (Rec. dist. 33 lks)
- A decayed Fir stump, bears N.75°W., 13 lks.

At the corner point

Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap marked:

T19S R9W  
S 7 S 8  
S 18 S 17  
1957

from which new BTs:

- A Hemlock, 6" dia., bears N.83½°E., 41 lks., mkd: T19S R9W S8 BT.
  - A Fir, 25" dia., bears S.54½°E., 67 lks., mkd: T19S R9W S17 BT.
- (Cont. next page)

TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 8, 17, & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir, 30" dia., bears N.13°W., 29 lks., mkd: T19S R9W S7  
BT.  
Deposit the corner stone alongside the iron post.

Fd. & used on BLM dependent resurvey by Donald R. Beck & Peter A. Peterson, Cadastral Surveyors, under Group #307, surveyed April 1968/Aug. 1976 (DCSO records Vol. 37 Page(s) 15461)

Fd. Ok by Robert Ward, Jr. - June 1991 - M113-37 A&B

Fd. & used on BLM dependent resurvey by Robert W. Dahl, Cadastral Surveyor, under Group #1450, surveyed Aug. 1988/May 23, 1991 - (DCSO records Vol. 49 Page(s) 18759)