TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 416-7)

Set a sandstone, 12x12x5 ins., 8 ins., in the ground for ¼ sec. cor., mkd: ¼ on W. face; from which
A Hemlock, 16" dia., bears N.77°E., 15 lks., mkd: ¼ S BT.
A Hemlock, 7" dia., bears N.76°W., 40 lks., mkd: ¼ S BT.
Old corner bears S.60°E., 150 lks.; I destroy
* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM dependent resurvey by Thomas A. Tillman, Robert L. Holm, & Floyd A. Brooks, under Group # 307, Surveyed May 1957 thru Sept. 1958 - (DCSO records Vol. 31 Page(s) 13063-64)

The ¼ sec. cor. of secs. 7 & 8, determined at record bearing & dist. from the remaining orig. BT:
A Hemlock stump, 24" dia., bears N.77°E., 15 lks., with scribe marks ¼ S8 visible on opened blaze.
At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

¼
S 7|S 8
1957

from which
A Fir, 22" dia., bears S.59°E., 118 lks., mkd: ¼ S8 BT.
No other suitable tree available.

Fd. ok by D. Baker, Sept. 1988 - M 107-1
Fd. ok by D. Baker, Nov. 1991 - M 114-27

Daniel Baker - For: Davidson Industries Inc - March 1997 - M 124-48

Found - US BLM Brass Cap 1957
34" Fir, S.59°E., 77.4', healed
Set - 15" Alder, N.55°W., 19.3', scribed "¼ S7 BT"
9" Hemlock N.38°E., 33.0', scribed "¼ S8 BT"
13" Alder, S.24°W., 46.0', scribed "¼ S7 BT"

Tony Hostetter - For: FIA Timber Partners II - 4/2016 - M172-22

Found - 2½" iron pie with 1957 BLM brass & BTs per rec.