

TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 422)

The ¼ sec. cor., established on former survey*, which is a post, 3 ft. long, 3" sq. set 24" in the ground, marked ¼ S20 on W and 21 on E faces; from which

A Fir, 7" dia., bears N.70°E., 29 lks., mkd: ¼ S BT.

A Fir, 6" dia., bears N.1°W., 67 lks., mkd: ¼ S BT.

* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM dependent resurvey by Donald R. Beck & Peter A. Peterson, Cadastral Surveyors, under Group #307, surveyed April 1968/Aug. 1976 (DCSO records Vol. 37 Page(s) 15456)

Point for ¼ sec. cor. of secs. 20 & 21, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

¼
S 20 S 21
T19S R9W
1969

from which

A Fir, 28" dia., bears N.87½°E., 48 lks., mkd: ¼ S21 BT.

A Fir, 23" dia., bears N.89°W., 24 lks., mkd: ¼ S20 BT.