

TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 423-24)

-----  
The cor. of secs 8, 9, 16, & 17, established on former survey\*, which is a post, 3 ft. long, 4" sq. 24" in the ground, marked T19S S9 on NE, R9W S16 on SE, S17 on SW and S8 on NW faces, with 4 notches on S & E edges; from which. face; from which

- A Fir, 5" dia., bears N.48°E., 100 lks., mkd: T19S R9W S9 BT.
- A Fir, 5" dia., bears S.32°E., 70 lks., mkd: T19S R9W S16 BT.
- A Fir, 5" dia., bears S.32°W., 21 lks., mkd: T19S R9W S17 BT.
- A Fir, 7" dia., bears N.75°W., 51 lks., mkd: T19S R9W S8 BT.

\* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM dependent resurvey by Donald R. Beck & Peter A. Peterson, Cadastral Surveyors, under Group #307, surveyed April 1968/Aug. 1976 (DCSO records Vol. 37 Page(s) 15458-59)

-----  
Point for sec. cor. of secs. & , at proportionate distance; there is no remaining evidence of the orig. corner.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T19S	R9W
S 8	S 9
S 17	S 16
1969	

from which

- A Hemlock, 23" dia., bears N.47½°E., 26 lks., mkd: T19S R9W S9 BT.
- A Hemlock, 13" dia., bears S.45°E., 16 lks., mkd: T19S R9W S16 BT.
- A Hemlock, 18" dia., bears S.42½°W., 22 lks., mkd: T19S R9W S17 BT.
- A Hemlock, 8" dia., bears N.25°W., 44 lks., mkd: T19S R9W S8 BT.

Fd. Ok by E. Alvarado, USFS - 12/6/1979 - C.S. File 60/34-29

(Cont. next page)

PRIMARY CORNER DESCRIPTION 8, 9, 16, & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 423-24)

-----  
The cor. of secs 8, 9, 16, & 17, established on former survey\*, which is a post, 3 ft. long, 4" sq. 24" in the ground, marked T19S S9 on NE, R9W S16 on SE, S17 on SW and S8 on NW faces, with 4 notches on S & E edges; from which face; from which


- A Fir, 5" dia., bears N.48°E., 100 lks., mkd: T19S R9W S9 BT.
- A Fir, 5" dia., bears S.32°E., 70 lks., mkd: T19S R9W S16 BT.
- A Fir, 5" dia., bears S.32°W., 21 lks., mkd: T19S R9W S17 BT.
- A Fir, 7" dia., bears N.75°W., 51 lks., mkd: T19S R9W S8 BT.

\* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM dependent resurvey by Donald R. Beck & Peter A. Peterson, Cadastral Surveyors, under Group #307, surveyed April 1968/Aug. 1976 (DCSO records Vol. 37 Page(s) 15458-59)

-----  
Point for sec. cor. of secs. & , at proportionate distance; there is no remaining evidence of the orig. corner.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:



- from which
- A Hemlock, 23" dia., bears N.47½°E., 26 lks., mkd: T19S R9W S9 BT.
  - A Hemlock, 13" dia., bears S.45°E., 16 lks., mkd: T19S R9W S16 BT.
  - A Hemlock, 18" dia., bears S.42½°W., 22 lks., mkd: T19S R9W S17 BT.
  - A Hemlock, 8" dia., bears N.25°W., 44 lks., mkd: T19S R9W S8 BT.

Fd. Ok by E. Alvarado, USFS - 12/6/1979 - C.S. File 60/34-29

(Cont. next page)

TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Michael J. Schwartz - For: USFS Siuslaw National Forest -  
July 1989 - M 108-53 A & B

-----

Found - 1969 BLM brass cap on a 2½" iron pipe projecting 16"  
out of the ground.  
27" Hemlock N.46 3/4°E., 17.0' scribing visible.1969  
14" Hemlock S.46½°E., 10.3' scribing visible. 1969  
25" Hemlock S.42 3/4°W., 14.3' scribing visible.1969  
10" Hemlock N.24 3/4°W., 28.6' scribing visible.1969  
Set - Reference monument: A USFS standard monument 28" in  
the ground, S.89°30'E., 64.3 ft. Stamped "RM T19S  
R9W S9 N89-30W 64.3 ft RLS1922 1989"