

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 425)

A Fir, 7" dia., for cor. of secs. 4, 5, 8, & 9, I mark T19S S4 on NE, R9W S9 on SE, S8 on SW and S5 on NW sides, with 5 notches on S & 4 notches on E sides; from which

- A Fir, 8" dia., bears N.69°E., 13 lks., mkd: T19S R9W S4 BT.
- A Fir, 8" dia., bears S.63°E., 9 lks., mkd: T19S R9W S9 BT.
- A Fir, 18" dia., bears S.50°W., 26 lks., mkd: T19S R9W S8 BT.
- A Fir, 9" dia., bears N.43°W., 6 lks., mkd: T19S R9W S5 BT.

BLM dependent resurvey by Donald R. Beck & Peter A. Peterson, Cadastral Surveyors, under Group #307, surveyed April 1968/Aug. 1976 (DCSO records Vol. 31 Page(s) 13060)

The cor. of secs. 4, 5, 8, & 9, mkd. by a Fir, 11" dia, plainly blazed & healed, from which the orig. BTs are as follows:

- A Fir snag, 10" dia., bears N.69°E., 13 lks., with healed blaze.
- A Fir, 12" dia., bears S.63°E., 9 lks., with healed blaze.
- A Fir, 28" dia., bears S.50°W., 26 lks., with healed blaze
- A Fir, 14" dia., bears N.33°W., 6 lks., with healed blaze. (Rec. bearing N.43°W.)

and a new BT

- A Fir, 20" dia., bears N.61¼°E., 50 lks., mkd: T19S R9W S4 BT.

Clyde Mulkins & Ronald Stuntzner - For: US Forest Service March 1983 - M 94-21 A-C

Found - Orig. corner tree, 11" D.Fir snag from which:

- 32" D.Fir bears S.50°W., 17.2 ft. w/healed face.
- 12" D.Fir bears S.63°E., 5.9 ft., open face w/ scribing: "R9W S9" visible. OBT
- 11" D.Fir snag bears N.69°E. 8.5' w/healed face. OBT
- 14" D.Fir bears N.35°W., 3.9 ft., w/healed face. OBT
- 24" D.Fir bears N.61¼°E. 33.0 ft. w/healed face 1958

Set - 2½"x30" aluminum pipe w/3" alum. cap, which is a standard USFS monument, for a reference monument mkd: RM T19S R9W S5 5.00→ S88°46'E S8 1983 PLS 2006, which bears N.88°46'W., 5.00 ft.

TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Please note that this corner is on the Douglas Co. & Lane Co. line and Lane Co. Surveyor's Office may have more information concerning this corner.

Tony Hostetter - For: FIA Timber Partners II - April 2016 - M172-22

Found - 11" fir stump corner tree, from which
2½" iron pipe with 1983 brass cap set as reference
monument by Mulkins & Stuntzner (M94-21 A&B)
bears N.88°42'24"W., 5.00 ft, rec. N.88°46'W.,
5.00 ft.
BTs described by Stuntzner present.