

TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 33 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705, dated April 14, 1899 - (DCSO records Vol. 44 Page(s) 17054)

-----  
In a ravine, course SE., Set a Fir post 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S33 on N. face, from which

An Alder 7" dia., bears N.70°W., 12 lks. dist. mkd. ¼ S BT.

An Alder 7" dia., bears N.19°E., 26 lks. dist. mkd. ¼ S BT.

Old cor. bears E., 6 lks. dist. I destroy it.

\* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated April 8, 1920 - (DCSO records Vol. 1 Page(s) 376)

-----  
(Apportioned distance) Set an iron post 3 ft. long, 1" dia., 27" in the ground, for re-established ¼ sec. cor. of sec. 33 only, with brass cap mkd:  $\frac{1}{4} S \frac{33}{1921}$

from which

A Fir 40" dia., bears N.32°E., 55 lks. dist. mkd. ¼ S33 BT

An Alder 8" dia., bears N.70°W., 8 lks. dist. mkd. ¼ S33 BT.