TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 433)

38.00 chs.
ld ¼ sec. cor.* bears South 14.00 chs., I destroy it.
39.95 chs.
A Fir, 12" dia., for ¼ sec. cor., I mark ¼ S4 on N and 9 on S sides; from which
A Fir, 14" dia., bears N.33°E., 26 lks., mkd: ¼ S BT.
A Fir, 12" dia., bears S.24°W., 8 lks., mkd: ¼ S BT.
* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM dependent resurvey by Thomas A. Tillman, Robert L. Holm, & Floyd A. Brooks, under Group # 307, Surveyed May 1957 thru Sept. 1958 - (DCSO records Vol. 31 Page(s) 13060-61)

Point for ¼ sec. cor. of secs. 4 & 9, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap marked:

¼ S 4 / S 9
T19S R9W
1958

from which
A Hemlock, 9" dia., bears N.55½°E., 41 lks., mkd: ¼ S4 BT.
A Fir, 25" dia., bears S.73½°W., 36 lks., mkd: ¼ S9 BT.

Please note that this corner is on the Douglas Co. & Lane Co. line and Lane Co. Surveyor's Office may have more information concerning this corner.