TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 33 & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 426)

The ¼ sec. cor., established on former survey*, which is a post 3 ft. long, 3" sq. set 24" in the ground, marked ¼ S33 on W and 34 on E faces; from which

A Fir, 8" dia., bears N.12°E., 16 lks., mkd: ¼ S BT.
A Fir, 9" dia., bears S.7°W., 30 lks., mkd: ¼ S BT.

* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM dependent resurvey by Donald R. Beck & Peter A. Peterson, Cadastral Surveyors, under Group #307, surveyed April 1968/Aug. 1976 (DCSO records Vol. 37 Page(s) 15441)

Point for ¼ sec. cor. of secs. 33 & 34, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

¼
S 33|S 34
T19S R9W
1969

from which

A Hemlock, 12" dia., bears N.43°E., 76 lks., mkd: ¼ S34 BT
A Maple, 22" dia., bears S.64°W., 42 lks., mkd: ¼ S33 BT.

Ronald L Rice - For: Oxbow Timber 1 LLC - 4/2016 - M170-76

Found - BLM brass cap dated 1969 with the following accessories:
32" Hemlock bears N.43°E 50.2' - healed face.
24" Maple bears S.64°W., 27.7' - healed face.
New BTs- 35" Maple bears N.16°E., 11.7' - blazed, scribed ¼ S34 BT
28" Maple bears N.20°E., 16.2' - blazed, scribed X BT
Steel post adjacent to corner