

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 426-27)

-----  
The corner of secs. 27, 28, 33, & 34, established on former survey\*, which is a post, 3 ft. long, 4" sq., set 24" in the ground, marked T19S S27 on NE, R9W S34 on SE, S33 on SW and S28 on NW faces, with 1 notch on S & 3 notches on E edges; from which

- A Fir, 5" dia., bears N.74°E., 12 lks., mkd: T19S R9W S27 BT.
- A Fir, 4" dia., bears S.5°E., 26 lks., mkd: T19S R9W S34 BT.
- A Fir, 8" dia., bears S.17°W., 40 lks., mkd: T19S R9W S33 BT.
- A Fir, 8" dia., bears N.3°W., 25 lks., mkd: T19S R9W S28 BT.

\* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM dependent resurvey by Donald R. Beck & Peter A. Peterson, Cadastral Surveyors, under Group #307, surveyed April 1968/Aug. 1976 (DCSO records Vol. 37 Page(s) 15441)

-----  
Point for ¼ sec. cor. at proportionate distance; there is no remaining evidence of the orig. corner.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T19S	R9W
S 28	S 27
S 33	S 34
1969	

from which

- A Fir, 35" dia., bears N.53°E., 42 lks., mkd: T19S R9W S27 BT.
- A Maple, 22" dia., bears S.75°E., 30 lks., mkd: T19S R9W S34 BT.
- A Maple, 20" dia., bears S.50°W., 148 lks., mkd: T19S R9W S33 BT.
- A Fir, 27" dia., bears N.32°W., 118 lks., mkd: T19S R9W S28 BT.

Ronald L Rice - For: Oxbow Timber 1 LLC - 4/2016 - M170-76

-----  
Found - BLM brass cap dated 1969 with the following accessories:

TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

38" D.Fir bears N.53°E., 27.7' - healed face.  
28" Maple bears S.75°E., 19.8' - healed face.  
24" Maple bears S.60°W., (Record S.50°W.) 97.7' -  
healed face.  
42" D.Fir bears N.32°W., 77.9' - healed face  
Steel post adjacent to corner