

TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 429)

The ¼ sec. cor., established on former survey*, which is a post, 3 ft. long, 3" sq., 24" in the ground, mkd: ¼ S21 on W and 22 on E faces; from which

A Fir, 10" dia., bears N.17°E., 80 lks., mkd: ¼ S BT.

A Fir, 8" dia., bears S.41°W., 63 lks., mkd: ¼ S BT.

* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM dependent resurvey by Donald R. Beck & Peter A. Peterson, Cadastral Surveyors, under Group #307, surveyed April 1968/Aug. 1976 (DCSO records Vol. 37 Page(s) 15445)

Point for ¼ sec. cor. of secs. 21 & 22, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 21" in the ground, with brass cap marked:

T19S R9W

¼

S 21 S 22

1968

from which

A Fir, 18" dia., bears N.79°E., 37 lks., mkd: ¼ S22 BT.

A Fir, 23" dia., bears N.18°W., 61 lks., mkd: ¼ S21 BT.