

TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 430)

The ¼ sec. cor., established on former survey*, which is post, 3 ft. long, 3" sq., 24" in the ground, mkd: ¼ S16 on W and 15 on E faces; from which

A Fir, 6" dia., bears N.60°E., 76 lks., mkd: ¼ S BT.

A Fir, 6" dia., bears N.12°W., 18 lks., mkd: ¼ S BT.

* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM dependent resurvey by Donald R. Beck & Peter A. Peterson, Cadastral Surveyors, under Group #307, surveyed April 1968/Aug. 1976 (DCSO records Vol. 37 Page(s) 15447)

Point for ¼ sec. cor. of secs. 15 & 16, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 21" in the ground, with brass cap marked:

T19S R9W
¼
S 16 S 15
1968

from which

A Fir, 44" dia., bears N.80½°E., 65 lks., mkd: ¼ S15 BT.

A Fir, 25" dia., bears S.44°W., 17 lks., mkd: ¼ S16 BT.