

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 430-31)

-----  
Set a sandstone, 12x8x8", 8" in the ground, for cor. of secs. 9, 10, 15, & 16, marked with 4 notches on S & 3 notches on E edges; from which

- A Fir, 5" dia., bears N.8°E., 25 lks., mkd: T19S R9W S10 BT.
- A Fir, 6" dia., bears S.60°E., 27 lks., mkd: T19S R9W S15 BT.
- A Fir, 4" dia., bears S.21°W., 30 lks., mkd: T19S R9W S16 BT.
- A Fir, 4" dia., bears N.40°W., 48 lks., mkd: T19S R9W S9 BT.

Old cor. bears S.20°E., 20 lks., I destroy it.  
\* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM dependent resurvey by Donald R. Beck & Peter A. Peterson, Cadastral Surveyors, under Group #307, surveyed April 1968/Aug. 1976 (DCSO records Vol. 37 Page(s) 15447-48)

-----  
Point for cor. of secs. 9, 10, 15 & 16, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T19S R9W  
S 9 S 10  
S 16 S 15  
1968

- from which
- A Fir, 11" dia., bears N.41°E. 19 lks. mkd: T19S R9W S10 BT
  - A Fir, 17" dia., bears S.30°E. 42 lks. mkd: T19S R9W S15 BT
  - A Fir, 22" dia., bears S.36°W. 26 lks. mkd: T19S R9W S16 BT
  - A Fir, 20" dia., bears N.38°W. 11 lks., mkd: T19S R9W S9 BT

Les Roberts - For: International Paper - July 1981 - M88-21

- Found - Brass cap (BLM) 1968-1969 resurvey  
15" Fir bears N.40½°E., 12.3 ft. (scar visible)  
18" Fir bears S.25°E., 27.9 ft. (scar visible)  
23" Fir bears S.34½°W., 17.3 ft. (scar visible)  
23" Fir bears N.39½°W., 6.6 ft. (scar visible)

Note - All BTs are from 1968 resurvey.

(Cont. next page)

TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Michael J. Schwartz - For: USFS Siuslaw National Forest -  
July 1989 - M 108-53 A & B

-----

Found - 1968 3¼" BLM brass cap is a 2½" iron pipe projecting  
12" out of the ground.  
15" Fir bears N.41°E., 12.2 ft., healed face. 1968  
16" Fir bears S.25¼°E., 27.6 ft. (scribing  
visible) 1968  
24" Fir bears S.35°W., 17.3 ft., healed face. 1968  
20" Fir bears N.38°W., 6.7 ft., healed face. 1968  
Set - Reference monument, a USFS standard monument 28" in  
the ground N.89°24'W., 50.2 ft. stamped "RM T19S  
R9W S16 S89-24E 50.2 ft. RLS1922 1989"