

TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 436)

Set a sandstone, 12x9x8 ins., 8 ins., in the ground for ¼ sec. cor., mkd: ¼ on W. face; from which
A Fir, 4" dia., bears N.59°E., 27 lks., mkd: ¼ S23 BT.
A Fir, 5" dia., bears S.10°W., 40 lks., mkd: ¼ S22 BT.

BLM dependent resurvey by Donald R. Beck & Peter A. Peterson, Cadastral Surveyors, under Group #307, surveyed April 1968/Aug. 1976 (DCSO records Vol. 37 Page(s) 15439)

Point for ¼ sec. cor. of secs. 22 & 23, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:
T19S R9W
¼
S 22 S 23
1968

from which
A Fir, 15" dia., bears S.49°E., 22 lks., mkd: ¼ S23 BT.
A Fir, 12" dia., bears S.81°W., 9 lks., mkd: ¼ S22 BT.