

TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 436)

-----  
On W. slope of mountain, 400 ft. above creek, the cor. of secs. 14, 15, 22, & 23, established on former survey\*, which is a sandstone, 16x9x8 ins., set 12" in the ground, marked with 3 notches on S & 2 notches E edges, with a mound of stone, 2 ft. base, 1½ ft. high, W of cor.

\* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM dependent resurvey by Thomas A. Tillman, Robert L. Holm, & Floyd A. Brooks, under Group # 307, Surveyed May 1957 thru Sept. 1958 - (DCSO records Vol. 31 Page(s) 13051-52)

-----  
Point for cor. of secs. 14, 15, 22, & 23, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T19S R9W  
S 15 S 14  
S 22 S 23  
1958

from which

- A Cedar, 7" dia., bears N.47°E., 74 lks., mkd: T19S R9W S14 BT.
- A Cedar, 8" dia., bears S.46°E., 42½ lks., mkd: T19S R9W S23 BT.
- A Fir, 23" dia., bears S.61°W., 70 lks., mkd: T19S R9W S22 BT.
- A Fir, 36" dia., bears N.35°W., 66 lks., mkd: T19S R9W S15 BT.

Fd. & used in BLM dependent resurvey by Donald R. Beck & Peter A. Peterson, Cadastral Surveyors, under Group #307, surveyed April 1968/Aug. 1976 (DCSO records Vol. 37 Page(s) 15440)