

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 438-39)

Set a sandstone, 16x7x6 ins., 12 ins., in the ground for cor. secs. 2, 3, 10, & 11, mkd. with 5 notches on S and 2 notches on E edges; from which

 A Fir, 8" dia., bears N.76°E., 28 lks., mkd: T19S R9W S2 BT.

 A Fir, 9" dia., bears S.30°E., 25 lks., mkd: T19S R9W S11 BT.

 A Fir, 12" dia., bears S.70°W., 30 lks., mkd: T19S R9W S10 BT.

 A Fir, 10" dia. bears N.61°W., 53 lks. mkd: T19S R9W S3 BT

Old cor. bears South 20 lks., I destroy it.

* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM dependent resurvey by Thomas A. Tillman, Robert L. Holm, & Floyd A. Brooks, under Group # 307, Surveyed May 1957 thru Sept. 1958 - (DCSO records Vol. 31 Page(s) 13054-55)

Point for cor. of secs. 2, 3, 10, & 11, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

	T19S	R9W
_____	S 3	S 2
_____	S 11	S 10
	1957	

from which

 A Fir, 32" dia. bears N.17°E., 60 lks. mkd: T19S R9W S2 BT

 A Fir, 35" dia. bears S.57°E., 49 lks mkd: T19S R9W S11 BT

 A Fir, 20" dia. bears S.39°W., 86 lks mkd: T19S R9W S10 BT

 A Fir, 32" dia. bears N.65°W., 35 lks. mkd: T19S R9W S3 BT

Ron Stuntzner - For: USFS - 8/1978 (Lane Co. - DCSO filed 12/30/2014) - C.S. File 65/86-37

Found - 2½" BCIP as set & marked in 1958 by BLM from which:

 38" D.Fir S.57°E., 49 lks.

 20" D.Fir snag S.39°W., 86 lks.

 32" D.Fir snag N.17°E., 60 lks.

 NW BT is a windfall

New - 40" D.Fir N.78°W., 43.4'.

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Rick A. McMullen, Cadastral Surveyor, under group #1512, surveyed Sept. 1989/June 1990 - (DCSO records Vol. 50 Page(s) 18942-43)

The cor. of secs. 2, 3, 10, and 11, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with properly marked brass cap.

from which remains of bearing trees mkd. by Tillman, Holm, and Brooks

A fir snag, 32 ins. diam., bears N.17°E., 58 lks., with scribe marks T19S R9W S2 B visible on open blaze. (Record, 60 lks.)

A sawed fir stump, 43 ins. diam., bears S.57°E., 43½ lks., with healed blaze. (Record, 49 lks.)

A sawed fir stump, 20 ins. diam., bears S.39°W., 81 lks., with scribe marks T19S R9W S10 BT visible on open blaze. (Record, 86 lks.)

A root hole, bears N.65°W., 35 lks., alongside of which is lying a sawed fir stump, 32 ins. diam., with scribe marks 9W 3 visible on open blaze.

and the remains of a bearing tree mkd. by person(s) unknown

A root hole, bears N.74¾°W., 67 lks., alongside of which is lying a fir, 41 ins. diam., with scribe marks 3 SE SC BT visible on open blaze.

and new bearing trees

A fir, 40 ins. diam., bears N.77°E., 59 lks., mkd. T19S R9W S2 BT.

A fir, 33 ins. diam., bears N.72°W., 156½ lks., mkd. T19S R9W S3 BT.

From this point, the Bureau of Land Management Control Station No. EC-41062, at latitude 43°56'35.458" N. and longitude 123°44'43.661" W. (NAD 1927), determined by the NAVSTAR Global Positioning System, bears S.52°35'42"E., 7.902 chs., monumented with an aluminum rod, 36 ins. long, ¾ in. diam., in PVC pipe filled with gravel, with an aluminum tablet, 3¾ ins. diam., firmly set flush with surface of the ground, mkd. EC 41062 1990 and a triangle.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2500, Surveyed Jan/March 2013 - (DCSO records Vol. 58 Page 23069 & **Survey plat 2014-1**)

The cor. of secs. 2, 3, 10, and 11, perpetuated by Stuntzner, in 1978; monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with a brass cap (properly) mkd.

from which the remains of the BTs mkd. by Tillman, Holm, and Brooks in 1957-58

continued next page

TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A decayed fir snag, 32" dia., bears N.17°E., 38.3 ft., with illegible scribe marks visible on a partially healed blaze.

A decayed fir stump, 40" dia., bears S.57°E., 28.7 ft., with a healed blaze.

A decayed fir stump, 19" dia., bears S.39°W., 53.5 ft., with scribe marks T19S R9W S10 BT visible on open blaze and the remains of a BT mkd. by Stuntzner (Record, person(s) unknown)

A roothole, bears N.74¼°W., 44.2 ft., downhill of which is an uprooted fir snag, 46" dia., with scribe marks 3 SE S visible on open blaze, and the BTs mkd. by McMullen in 1989-90

A fir, 47" dia., bears N.77°E., 38.9 ft., with a healed blaze.

A fir, 40" dia., bears N.72°W., 103.3 ft., with a healed blaze.

and new bearing trees

A fir, 9" dia. bears S.18°E., 6.7 ft. mkd. T19S R9W S11 BT

A fir, 9" dia., bears S.80½°W., 54.4 ft., mkd. T19S R9W S10 BT.

Latitude 43°56'38.02"N. Longitude 123°44'53.66"W. NAD 1983 (2011)

Please note that this corner is on the Douglas Co. & Lane Co. line and Lane Co. Surveyor's Office may have more information concerning this corner.