

TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION WC 1/4 Cor Secs 26 & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Eimstad & Associates - For: International Paper - May 1978 - M 72-15

Found - Witness corner to ¼ cor. 1961 Douglas Co. brass cap & 3/4" rod bears S.70°12'37"W., 48.75 ft & ¼ cor. N.70°12'37"E., 130.0 ft.
Set - 5/8"x24" rebar in road for ¼ corner.
Concrete nail in lead in rock wall, N.80°W., 59.19'
5/8"x30" rebar in rock seam, S.15°W., 41.92 ft.

Jerry Estabrook - For: Roseburg Resources Co. - 4/2021 - M179-32

Found - WC: A 1½" iron pipe with 2½" brass cap md: "T19S R9W ¼ S26 S35 WC N.70°E., 130 ft to cor 1961" per CS File 52/94. WC monument bears S.70°W., 130.00' from ¼ corner. A ¾" iron rod bears S.70°W., 48.25' from WC.
New BTs marked for 1/4 corner -
A 12" Alder, bark scribed "N¼ S35 BT" with X- chop and tag bears S.61°E., 23.0' to a spike at side center.
A 20" Fir face scribed "N¼ S35 BT" with X-chop & tag bears S.07°W., 62.3' to a spike at side center.
New B0 tied -
A steel post bears north 18.8'.
Found BT for WC -
A 61" Fir with healed face and tag bears S.68°W., 48.3'.
Found B0 for WC -
A ¾" iron rod bears S.70°W., 48.25'.
LAT and LONG per GARM1N ETREX HAND HELD GPS -
N: 43°53'05.6" W: 123°44'16.9"