TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 446-7)

On summit of divide bet. N fork of Smith River & Whittaker Creek, 150 ft. above last ravine, bears N. and S.
Set a Fir post, 3 ft. long, 3" sq. 24 ins., in the ground for ¼ sec. cor., mkd: ¼ S11 on N. and 14 on S. faces; from which
A Fir, 12" dia., bears N.19°E., 9 lks., mkd: ¼ S BT.
A Fir, 6" dia., bears S.10°W., 40 lks., mkd: ¼ S BT.
Old cor. bears S.83°W., 17 lks., I destroy it.
* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM dependent resurvey by Thomas A. Tillman, Robert L. Holm, & Floyd A. Brooks, under Group # 307, Surveyed May 1957 thru Sept. 1958 - (DCSO records Vol. 31 Page(s) 13053)

Point for ¼ sec. cor. of secs. 11 & 14, at proportionate distance; there is no remaining evidence of the orig. corner.
Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap marked:

¼ S 11
S 14
1958

from which
A Fir, 32" dia., bears N.57°W., 69 lks., mkd: ¼ S11 BT.
A Fir, 34" dia., bears S.79°W., 36 lks., mkd: ¼ S14 BT.