

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36 only, (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705, dated April 14, 1899 - (DCSO rec Vol 1 Pg 370)

-----

Set a post 3 ft. long, 4" sq., 24" in the ground cor. of secs.35 & 36, marked T19S S36 on NE.; and R9W S35 on NW. faces, with 1 notch on E. & 5 notches on W. edges; from which

A Cherry 7" dia. bears N.82½°E. 30 lks mkd T19S R9W S36 BT

A Cherry 8" dia. bears N.63°W., 22 lks mkd T19S R9W S35 BT

Old cor. bears E. 4 lks. dist., I destroy it.

\* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM Resurvey by Thomas A. Tillman and Joseph S. Gawron, Cadastral Engineers, under Group #306, surveyed May 1953/Oct. 1954 - (DCSO records Vol. 29 Page(s) 12458-59)

-----

The cor. of secs. 35 & 36, T19-9 determined from the remaining original bearing tree as follows:

A Cherry snag 7" dia., bears N.82½°E., 30 lks. plainly blazed and healed.

At the corner point

Set an iron post 3 ft. long, 2" dia., 28" in the ground with brass cap mkd:

T 19 S R 9 W
S 35   S 36
T 20 S R 9 W
S 2
1953

from which new bearing tree

An Alder 13" dia bears N.4½°E., 55 lks mkd T19S R9W S36 BT

A Fir 43" dia., bears N.45°W., 73 lks mkd. T19S R9W S35 BT

Ron Rice, NW Land Surveying - Jason Collver - May 2012 - C.S. File 65/76-46 & M167-71 (2/2014)

-----

Found - 2½" GLO brass cap on iron pipe, dated 1953

Alder 13" dia., bears N.4½°E., 55 lks. mkd. T19S R9W S36 BT. (Missing)

Fir 43" dia., bears N.45°W., 73 lks. mkd. T19S R9W S35 BT. (Missing)

New - 24" D. Fir bears S.7°E., 18.4 ft. blazed, scribed, T19S R9W S36 BT

21" D. Fir bears N.67°W., 22.8 ft. blazed, scribed, T19S R9W S35 BT

Note - Corner has steel post adjacent to it. All BTs have red painted bands and yellow tags.

Cont.

TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36 only, (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Eugene Wobbe - Crew: Brad Foster & Matthew Ternyik - 7/7/2017  
- C.S. File 65/95-43

-----

- Found - 2½" brass cap (properly mkd) on 2" iron post with steel post alongside.  
24" D.Fir now 25" with healed face bears N.9°E., 18.4' (Rec. S.7°E.) - 2012 BT
- 21" D.Fir now 22" with healed face bears N.67½°W., 22.8' - 2012 BT
- New - Set alum. channel marker post with BLM land survey marker sign North 3' from corner.
- Note - Bearings are based on 1958 BLM survey.