

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 2 Page(s) 442)

-----  
The cor. of secs. 23, 24, 25, & 26, established on former survey\*, which is a basalt stone, 16x8x8 ins., 12 ins. in the ground, mkd. with 2 notches on S & 1 notch on E edges, with a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

\* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM dependent resurvey by Donald R. Beck & Peter A. Peterson, Cadastral Surveyors, under Group #307, surveyed April 1968/Aug. 1976 (DCSO records Vol. 37 Page(s) 15432-3)

-----  
Point for cor. of secs. 23, 24, 25, & 26, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap marked:

T19S R9W  
S 23 S 24  
S 26 S 25  
1968

- A Hemlock, 8" dia., bears N.60°E., 34 lks., mkd: T19S R9W S24 BT.
- A Fir, 27" dia., bears S.54½°E., 35 lks., mkd: T19S R9W S25 BT.
- A Hemlock, 13" dia., bears S.77°W., 54 lks., mkd: T19S R9W S26 BT.
- A Fir, 26" dia., bears N.50½°W., 55 lks., mkd: T19S R9W S23 BT.

BLM dependent resurvey by John P. Farnsworth, Cadastral Surveyor, under Group #1076, surveyed Sept. 1981/April 1983 - (DCSO records Vol. 45 Page(s) 17472-73)

-----  
From the cor. of secs. 23, 24, 25, & 26, monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with properly mkd. brass cap.

from which the remains of BTs mkd. by Beck & Peterson:

- A Fir snag., 9" dia., bears N.65°E., 34 lks., with scribe marks: T19S R9W S24 BT visible on partially healed blaze. (Rec. Hemlock, N.60°E.)

(Cont. next page)

TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir, 30" dia., bears S.54½°E., 35 lks., with healed blaze.  
A Fir, 30" dia., bears N.50½°W., 55 lks., with healed blaze.  
and new BTs  
A Fir, 15" dia., bears N.76¼°E., 82½ lks., mkd: T19S R9W S24 BT.  
A Fir, 25" dia., bears S.61 3/4°W., 91 lks., mkd: ¼ S26 BT.