

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 444)

-----  
Set a basalt stone, 16x6x6 ins., 12 ins., in the ground for 1/4 sec. cor., mkd: 1/4 on W. face; and raised a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor. No trees within limits. The old cor. bears East, 11 lks.; I destroy it.  
\* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM dependent resurvey by Donald R. Beck & Peter A. Peterson, Cadastral Surveyors, under Group #307, surveyed April 1968/Aug. 1976 (DCSO records Vol. 37 Page(s) 15435)

-----  
Point for 1/4 sec. cor. of secs. 23 & 24, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2 1/2" dia., 21" in the ground, with brass cap marked:  
T19S R9W  
1/4  
S 23 S 24  
1968

from which  
A Hemlock, 13" dia., bears N.31 1/2° E., 57 lks., mkd: 1/4 S23 BT.  
A Hemlock, 11" dia., bears N.16° W., 43 lks., mkd: 1/4 S24 BT.

BLM dependent resurvey by John P. Farnsworth, Cadastral Surveyor, under Group #1076, surveyed Sept. 1981/April 1983 - (DCSO records Vol. 45 Page(s) 17477)

-----  
The 1/4 sec. cor. of secs. 23 & 24, monumented with an iron post, 2 1/2" dia., firmly set, projecting 6" above ground, with properly marked brass cap.  
from which BTs mkd. by Beck & Peterson  
A Fir, 16" dia., bears N.35 1/4° E., 57 lks., with healed blaze. (Rec. Hemlock, N.31 1/2° E.)  
A Fir, 14" dia., bears N.13 1/2° W., 43 lks., with healed blaze. (Rec. Hemlock, N.16° W.)