

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 14, 23, & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 444)

Set a basalt stone, 18x9x6 ins. 14" in the ground, for cor. secs. 13, 14, 23, & 24, marked with 3 notches on S & 1 notch on E edges; and raised a mound of stone, 2 ft. base, 1½ ft. high, W. of corner. No trees within limits. The old corner bears W. 7 lks.; I destroy it.
 * 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM dependent resurvey by Thomas A. Tillman, Robert L. Holm, & Floyd A. Brooks, under Group # 307, Surveyed May 1957 thru Sept. 1958 - (DCSO records Vol. 31 Page(s) 13041)

The point for the corner of secs. 13, 14, 23, & 24, is determined at double proportionate distance.
 Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T19S R9W
S 14°S 13
 S 23°S 24
 1958

from which

- A Fir, 15" dia., bears N.28¾°E., 55 lks., mkd: T19S R9W S13 BT.
- A Fir, 8" dia., bears S.4½°E., 27 lks., mkd: T19S R9W S24 BT.
- A Fir, 7" dia., bears S.54°W., 39 lks., mkd: T19S R9W S23 BT.
- A Fir, 15" dia., bears N.27¼°W., 35 lks., mkd: T19S R9W S14 BT.

Fd. & used on BLM dependent resurvey by Donald R. Beck & Peter A. Peterson, Cadastral Surveyors, under Group #307, surveyed April 1968/Aug. 1976 (DCSO records Vol. 37 Page(s) 15435-6)

Fd. & used on BLM dependent resurvey by John P. Farnsworth, Cadastral Surveyor, under Group #1076, surveyed Sept. 1981/April 1983 - (DCSO records Vol. 45 Page(s) 17477-8)

Robert Ward - May 2002 filed Oct. 2013 - C.S. File 65/80-9

Fd BC & 4 BTs.