

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 446)

The 1/4 sec. cor., established on former survey*, which is a basalt stone, 12x8x7 ins., set 8 ins. in the ground, marked 1/4 on W. face; from which

A Fir, 12" dia., bears N.43°W., 18 lks., mkd: 1/4 S14 BT.

A Fir, 14" dia., bears N.68°E., 10 lks., mkd: 1/4 S13 BT.

* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM dependent resurvey by Thomas A. Tillman, Robert L. Holm, & Floyd A. Brooks, under Group # 307, Surveyed May 1957 thru Sept. 1958 - (DCSO records Vol. 31 Page(s) 13042)

Point for 1/4 sec. cor. of secs. 13 & 14, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap marked:

T19S R9W
1/4
S 14*S 13
1958

from which

A Fir, 7" dia., bears N.82°E., 42 1/2 lks., mkd: 1/4 S13 BT.

A Fir, 22" dia., bears S.84°W., 27 lks., mkd: 1/4 S14 BT.

Robert Ward - May 2002 filed Oct. 2013 - C.S. File 65/80-8

Found - 2 1/2" dia., brass cap dated 1958
27" fir, now uprooted.
24" fir bears S.84 1/4°W., 17.7 ft. now a high stump with visible scribing.

New - 10" alder bears N.76 1/4°E., 24.3 ft scribed "1/4 S13 BT"

10" hemlock bears N.79 1/2°W., 23.8 ft. scribed "1/4 S14 BT"

10" hemlock bears S.71 1/2°E., 31.3 ft. scribed "1/4 S13 BT"