TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 448)

Set a basalt stone, 12x8x8 ins., 8 ins., in the ground for ¼ sec. cor., mkd: ¼ on W. face; from which
A Fir, 6" dia., bears N.50°E., 20 lks., mkd: ¼ S12 BT.
A Fir, 6" dia., bears S.32°W., 40 lks., mkd: ¼ S11 BT.
Old cor. bears N.69°E., 16 lks., I destroy it.
* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM dependent resurvey by Thomas A. Tillman, Robert L. Holm, & Floyd A. Brooks, under Group # 307, Surveyed May 1957 thru Sept. 1958 - (DCSO records Vol. 31 Page(s) 13044-5)

Point for ¼ sec. cor. of secs. 11 & 12, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap marked:

¼
S 11*S 12
1958

from which
A Fir, 12" dia., bears S.35°E., 23 lks., mkd: ¼ S12 BT.
A Fir, 23" dia., bears N.40°W., 28 lks., mkd: ¼ S11 BT.

Ron Rice - For: Plum Creek - Feb. 2014 - M167-43

Found - 3¼" BLM brass cap dated 1958 with the following accessories:
12" Fir stump bears S.35°E. 15.2' - scribing visible
31 Fir bears N.40°W., 18.5' BLM tag dated 1975 reads N.39°W., 19.0' - healed face
Unrecorded 1975 BLM BT FD
24" Fir bears S.2°W., 56.3' - healed face
Steel post adjacent to corner