

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 448)

-----

Set a basalt stone, 13x6x6 ins., 8 ins., in the ground for cor. of secs. 1, 2, 11, & 12, mkd. with 5 notches on S & 1 notch on E edges; and raised a mound of stone, 2 ft. base, 1½ ft. high, W of corner. No trees within limits.  
 Old cor. bears S.40°E., 12 lks., I destroy it.  
 \* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM dependent resurvey by Thomas A. Tillman, Robert L. Holm, & Floyd A. Brooks, under Group # 307, Surveyed May 1957 thru Sept. 1958 - (DCSO records Vol. 31 Page(s) 13045)

-----

Point for cor. of secs. 1, 2, 11, & 12, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T19S	R9W
<u>S</u>	<u>2*S</u> <u>1</u>
S	11*S 12
	1957

- from which
- A Fir, 32" dia., bears N.6½°E., 33 lks., mkd: T19S R9W S1 BT.
  - A Fir, 25" dia., bears S.72¼°E., 34 lks., mkd: T19S R9W S12 BT.
  - A Fir, 33" dia., bears S.44°W., 63 lks., mkd: T19S R9W S11 BT.
  - A Fir, 25" dia., bears N.63°W., 36 lks., mkd: T19S R9W S2 BT.

BLM dependent resurvey by Rick A. McMullen, Cadastral Surveyor, under group #1512, surveyed Sept. 1989/June 1990 - (DCSO records Vol. 50 Page(s) 18939-40)

-----

From the cor. of secs. 1, 2, 11 and 12, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with properly marked brass cap.  
 from which remains of bearing trees mkd. by Tillman, Holm, & Brooks

- A fir, 41 ins. diam., bears N.6½°E., 33 lks., with healed blaze.
- A fir, 32 ins. diam., bears S.72¼°E., 31 lks., with healed blaze. (Record, 34 lks.) (Cont. next page)

TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 38 ins. diam., bears S.44°W., 63 lks., with healed blaze.  
A sawed fir stump, 30 ins. diam., bears N.63°W., 36 lks., with scribe marks R9W S2 BT visible on opened blaze.  
No other suitable trees available in sec. 2.

Fd. BC & BTs; & steel post adjacent to corner by R. Rice  
2/2014 - M167-43

Please note that this corner is on the Douglas Co. & Lane Co. line and Lane Co. Surveyor's Office may have more information concerning this corner.