

TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO rec Vol 1 Pg 441)

The 1/4 sec. cor. established on former survey*, which is a basalt stone, 16x7x7 ins., set 12" in the ground, mkd: 1/4 on N face; from which
 A Fir, 7" dia., bears N.80°E., 7 lks., mkd: 1/4 S25 BT.
 A Fir, 5" dia., bears S.6°E., 15 lks., mkd: 1/4 S36 BT.
* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM dependent resurvey by Thomas A. Tillman, Robert L. Holm, & Floyd A. Brooks, under Group # 307, Surveyed May 1957 thru Sept. 1958 - (DCSO records Vol. 31 Page(s) 13039-40)

Point for 1/4 sec. cor. of secs. 25 & 36, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap marked:
 1/4 $\frac{S\ 25}{S\ 36}$
 T19S R9W
 1958
from which
 An Alder, 22" dia., bears N.50 3/4°W., 79 lks., mkd: 1/4 S25 BT
 A Maple, 20" dia., bears S.67°E., 16 lks., mkd: 1/4 S36 BT.

Ron Rice, NW Land Surveying - Jason Collver - May 2012 - C.S. File 65/76-49

Found - 3 3/4" BLM brass cap on iron pipe, dated 1958
 An Alder, 22" dia., bears N.50 3/4°W., 79 lks., mkd: 1/4 S25 BT. (Missing)
 A Maple, 20" dia., bears S.67°E., 16 lks., mkd: 1/4 S36 BT. (Missing)
New - 18" D.Fir bears N.54°W., 18.1 ft. blazed, scribed, 1/4 S25 BT
 11" D.Fir bears N.11°E., 25.8 ft. blazed, scribed, 1/4 S25 BT
 11" D.Fir bears N.83°E., 39.2 ft. blazed, scribed, 1/4 S25 BT
 14" Red Cedar bears S.30°W., 20.0 ft. blazed, scribed, 1/4 S36 BT
Note - Corner has steel post adjacent to it. All BTs have red painted bands and yellow tags.
 Compass Declination 16° East

CONT.

TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Jerry Estabrook - For: Roseburg Resources - 4/2022 - M180-74
& C.S. 65/109-58 (1977 BLM Admin Survey)

Found - 2½" Iron pipe with ¾" brass cap mkd: ¼ S25 S36 T19S
R9W 1958, per record, with steel post alongside.
22" Fir with healed face & tag bears N.54°W., 18.1'
11" Fir with healed face & tag bears N.11°E., 25.8'
14" Fir with healed face & tag bears N.83°E., 39.2'
16" R.Cedar with healed face and tag bears S.30°W.,
20.0'

Garmin Etrex Hand held GPS:

Lat: N 43°53'06.7" Long: W 123°43'04.7"

Fd ok by Tony Hostetter - June 2024 - M184-72