

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 24 & 25

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 443)

The 1/4 sec. cor., established on former survey*, which is a basalt stone, 16x7x7 ins., 12 ins. in the ground, marked 1/4 on N. face; from which

A Fir, 6" dia., bears N.75°W., 14 lks., mkd: 1/4 S24 BT.

A Fir, 5" dia., bears S.7°E., 23 lks., mkd: 1/4 S25 BT.

* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM dependent resurvey by Donald R. Beck & Peter A. Peterson, Cadastral Surveyors, under Group #307, surveyed April 1968/Aug. 1976 (DCSO records Vol. 37 Page(s) 15433)

Point for 1/4 sec. cor. of secs. 24 & 25, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2 1/2" dia., 21" in the ground, with brass cap marked:

T19S R9W

1/4 S 24
S 25

1968

from which

A Fir, 36" dia., bears N.2°E., 17 lks., mkd: 1/4 S24 BT.

A Fir, 42" dia., bears S.30°E., 9 lks., mkd: 1/4 S25 BT.

BLM dependent resurvey by John P. Farnsworth, Cadastral Surveyor, under Group #1076, surveyed Sept. 1981/April 1983 - (DCSO records Vol. 45 Page(s) 17473-74)

Point for 1/4 sec. cor. of secs. 24 & 25, at proportionate distance; there is no remaining evidence of the orig. corner. From this point, the 1/4 sec. cor. of secs. 24 & 25, erroneously positioned by Beck & Peterson, bears N.8°35'W., 0.214 chs. monumented with an iron post, 2 1/2" dia., firmly set, projecting 6" above ground, with brass cap mkd. & witnessed as described in the official record.

I remove the iron post, destroy the marks on the SE BT and at the true corner point.

reset the iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap marked:

(Cont. next page)

TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 24 & 25

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

T19S R9W
 $\frac{1}{4}$ S 24
 S 25
 1983
 1968

from which a BT mkd. by Beck & Peterson
 A Fir, 39" dia., bears N.4°W., 38 lks., with healed
 blaze.
and a new BT
 A Maple, 23" dia., bears S.43°W., 34 lks., mkd: $\frac{1}{4}$ S25
 BT.