

TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 445)

-----  
Set a basalt stone, 14x9x6 ins., 9 ins., in the ground for ¼ sec. cor., mkd: ¼ on N. face; and raised a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

The old cor. bears S.79°W., 11 lks., I destroy it.

\* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM dependent resurvey by Thomas A. Tillman, Robert L. Holm, & Floyd A. Brooks, under Group # 307, Surveyed May 1957 thru Sept. 1958 - (DCSO records Vol. 31 Page(s) 13041)

-----  
Point for ¼ sec. cor. of secs. 13 & 24, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T19S R9W  
¼     S 13  
       S 24  
       1958

from which

A Fir, 8" dia., bears N.77°E., 33 lks., mkd: ¼ S13 BT.

A Fir, 30" dia., bears S.54½°W., 31 lks., mkd: ¼ S24 BT.

Fd. & used on BLM dependent resurvey by John P. Farnsworth, Cadastral Surveyor, under Group #1076, surveyed Sept. 1981/April 1983 - (DCSO records Vol. 45 Page(s) 17475)