

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 1 Page(s) 405)

Fir 24" dia., which I mark for ¼ sec. cor., ¼ S on W. face; from which

A Fir 40" dia., bears N.76°E., 16 lks. dist. mkd. ¼ S BT.

A Fir 36" dia., bears N.69°W., 25 lks. dist. mkd. ¼ S BT.

BLM Resurvey by Thomas A. Tillman and Joseph S. Gawron, Cadastral Engineers, under Group #306, surveyed May 1953/Oct. 1954 - (DCSO records Vol. 29 Page(s) 12456-57)

The ¼ sec.cor., marked by the stump hole of the corner tree, an uprooted Fir, 30" dia., bearing a healed blaze on one side; from the corner point, the original bearing trees:

An uprooted Fir 50" dia., plainly blazed and healed, the stump hole of which bears N.76°E., 16 lks. dist.

A Fir snag 30" dia., bears N.69°W., 25 lks. dist., with scribe marks ¼ S BT visible on partly healed blaze.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 34" in the ground, with brass cap mkd:

| ¼ S 31
1953

from which new bearing trees:

A Dogwood 12" dia., bears N.9°E., 26 lks. mkd. ¼ S31 BT.

A Fir 40" dia., bears S.37°E., 96 lks. mkd. ¼ S31 BT.

Cor. Fd. OK and used in BLM Resurvey by Thomas A. Tillman; Robert L. Holm & Floyd A. Brooks, Cadastral Surveyors, under Group #307, surveyed May 1957/Sept. 1958 - (DCSO records Vol. 31 Page(s) 13016)

BLM dependent resurvey by Edith M Forkner & Jason A Lightbown, Cadastral Surveyors, under Group #2820, surveyed Feb./June 2016 - (DCSO records Vol. 59 Page(s) 23531-2)

The ¼ sec. cor. of sec. 31 only, determined at record bearing and dist. from the remains of a bearing tree mkd. by Tillman and Gawron in 1953-54

A decayed fir stump, 37" dia., bears S.37°E., 63.4 ft., with illegible scribe marks visible on partially healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, with brass cap mkd.

continued next page

TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 700102

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 31 only, T19-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

T 19 S
R 9 W | R 8 W
 | ¼ S 31
 2016

from which new bearing trees

 A fir, 13" dia., bears N.50°E., 7.1 ft., mkd. ¼ S31 BT.

 A fir, 10" dia., bears S.33½°E., 10.3 ft., mkd. X at
 breast height and BT at the base.

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at
the base right side-center & has a magnet deposited in a
white plastic case at the base of the stainless steel post.
Alum. angle iron driven alongside each corner.