

TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 36 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM survey by Thomas A. Tillman; Robert L. Holm & Floyd A. Brooks, Cadastral Surveyors, under Group #307, surveyed May 1957/Sept. 1958 - (DCSO records Vol. 31 Page(s) 13017)

Point for the ¼ sec. cor. of sec. 36 only, on the E. bdy. of T19-9, at midpoint between closing corners.

Set an iron post 3 ft. long, 2" dia., 28" in the ground with brass cap mkd.

T 19 S
¼ S 36
R 9 W
1957

from which

A Fir 22" dia., bears N.22°W., 13 lks. dist. mkd. ¼ S36 BT.

A Fir 8" dia., bears S.47°W., 83 lks. dist. mkd. ¼ S36 BT.

Fd. OK, June 5, 1981 by L. Roberts - M 87-78

BLM dependent resurvey by Edith M Forkner & Jason A Lightbown, Cadastral Surveyors, under Group #2820, surveyed Feb./June 2016 - (DCSO records Vol. 59 Page(s) 23532)

The ¼ sec. cor. of sec. 36 only, T19S R9W monumented with an iron post, 2" dia., firmly set, projecting 8 ins. above ground, with a brass cap (properly) mkd.

from which the BTs mkd. by Tillman, et al. in 1957-58

A fir, 14" dia., bears S.48°W., 55.7 ft., with a healed blaze. (Record, S.47°W., 54.8 ft.)

A fir, 31" dia., bears N.22°W., 8.6 ft., with a healed blaze.

Fd ok by Tony Hostetter - June 2024 - M184-72