

TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION C C for Secs. 25 & 36, (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705, dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 441)

Intersect the W. bdy. of T19S R8W, at the closing cor. of secs. 25 & 36, established on former survey*, which is a basalt stone 12x8x7 ins., 8" in the ground, mkd. CC on W. face, with 1 notch on S. and 5 notches on N. edges; from which

A Fir 12" dia., bears N.73°W., 29 lks. dist. mkd. T19S R9W S25 BT.

A Fir 10" dia., bears S.19½°W., 22 lks. dist. mkd. T19S R9W S36 BT.

(This closing cor. is 2.29 chs. S. of the ¼ sec. cor. on W. bdy. of sec. 30, T19S R8W)

* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM survey by Thomas A. Tillman; Robert L. Holm & Floyd A. Brooks, Cadastral Surveyors, under Group #307, surveyed May 1957/Sept. 1958 - (DCSO records Vol. 31 Page(s) 13018-19)

Point for the closing sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 19 S T 19 S
CC $\frac{S\ 25}{S\ 36}$ S 30
R 9 W R 8 W
1957

from which

A Fir 40" dia., bears N.75°W., 28 lks. dist., mkd. T19S R9W S25 CC BT.

A Fir 26" dia., bears S.71°W., 88 lks. dist. mkd. T19S R9W S36 CC BT.

Fd. OK, June 5, 1981 by L. Roberts - M 87-78

Survey by Les Roberts, LS #1039 - For: International Paper Co. - Jan. 1985 - M 98-19 and C.S. File 58/293

Found - 1957 GLO brass cap destroyed by cat road.
50" Fir N.74°W., 18.6 ft., scar visible. (1899 BT rec., N.73°W., 19.1 ft.)

(Cont. Next Page)

TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION C C for Secs. 25 & 36, (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

26" downed Fir, S.71°W., 58.1 ft., scribe visible.
(1957 BT rec., S.71°W., 58.1 ft.)
Set 2½" x 30" alum. pipe and cap. Buried purple magnetic marker under alum. pipe. Cor. set S.0°01'21"W., 152.34 ft. from found W. ¼ cor. of sec. 30.
New BT - 42" Fir stump S.15°E., 53.7 ft. to RR spike. Painted alum. washer.
Set metal fence post next to brass cap. Wired land survey monument sign to fence post.
Cor. lies in cat road on gentle S. slope. New logged unit lies to East.

BLM dependent resurvey by Edith M Forkner & Jason A Lightbown, Cadastral Surveyors, under Group #2820, surveyed Feb./June 2016 - (DCSO records Vol. 59 Page(s) 23534)

The closing cor. of secs. 25 & 36, T19S R9W perpetuated by Roberts, in 1985; monumented with an aluminum post, 2½" dia., firmly set, with top flush with the surface of the ground, with an aluminum cap (properly) mkd.
from which the remains of the BTs mkd. by Tillman, et al. in 1957-58
Decayed fir remains within a roothole, size indeterminate, bears S.71°W., 58.1 ft., no marks visible, alongside of which is a down decayed fir, size indeterminate, no marks visible.
A fir, 54" dia., bears N.75°W., 18.5 ft., no marks visible and a washer mkd. PLS 1039 nailed to the face.
and the remains of a bearing tree mkd. by Roberts
A decayed fir stump, 25" dia., bears S.16°E., 55.3 ft., no marks visible.
and a new bearing tree
A fir, 11" dia., bears S.25½°W., 32.5 ft., mkd. T19S R9W S36 CC BT.
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. angle iron driven alongside each corner.

Corner is located in a skid road, bears N. and S. A steel fence post with a USFS sign is alongside the monument.