

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 30 only, T19-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 1 Page(s) 406)

Set post 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on W. face; from which
A Fir 40" dia., bears S.20½°W., 66 lks. dist. mkd. ¼ S BT
A Maple 16" dia., bears N.33 ¾°E. (distance omitted)

BLM survey by Thomas A. Tillman; Robert L. Holm & Floyd A. Brooks, Cadastral Surveyors, under Group #307, surveyed May 1957/Sept. 1958 - (DCSO records Vol. 31 Page(s) 13019)

The ¼ sec. cor., determined from the original bearing trees:
A Maple 20" dia., bears N.36¼°E., 92 lks. dist., with no scribe marks visible on opened blaze. (Rec. brg. N.33 ¾°E. (distance omitted in original notes)
A sawed Fir stump 48" dia., bears S.20½°W., 66 lks. dist., with scribe marks scaled off distinct bark blaze.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 19 S
¼ S 30
R 8 W
1957

from which

A Maple 15" dia., bears N.48 ¾°E., 36 lks. dist. mkd. ¼ S30 BT.

A Hemlock 20" dia., bears S.11 ¾°E., 18 lks. dist. mkd. ¼ S30 BT.

Survey by Les Roberts, LS #1039 - For: International Paper Co. - Jan. 1985 - M 98-19 and C.S. File 58/293

Found - 1957 GLO brass cap, set firmly in ground.
44" Fir stump S.20¼°W., 43.0 ft., scar visible. (1891 BT, rec. S.20½°W., 43.6 ft.)
15" Maple N.48 ¾°E., 24.2 ft., scribe visible. (1957 BT, rec. N.48 ¾°E., 23.8 ft.)
22" Hemlock snag S.11 ¾°E., 11.7 ft., scribe visible. (1957 BT, rec. S.11 ¾°E., 11.9 ft.)

New BT - 24" Fir stump S.78°E., 30.4 ft. to RR spike with painted alum. washer.

Set metal fence post next to brass cap. Wired land survey monument sign to fence post.

Cor. lies on gentle S. slope. New logged unit lies to East.

continued next page

TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 700202

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 30 only, T19-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Edith M Forkner & Jason A Lightbown, Cadastral Surveyors, under Group #2820, surveyed Feb./June 2016 - (DCSO records Vol. 59 Page(s) 23534-5)

The ¼ sec. cor. of secs. 30 only, perpetuated by Roberts, in 1985; monumented with an iron post, 2" dia., firmly set, projecting 8" above ground, with a brass cap (properly) mkd. from which the remains of an original bearing tree

A decayed fir stump, 46" dia., bears S.20½°W., 43.6 ft., no marks visible.

and a bearing tree mkd. by Tillman, et al. in 1957-58

A maple, 17" dia., bears N.48¾°E., 23.8 ft., with no marks visible on decayed partially healed blaze.

and the remains of a bearing tree mkd. by Roberts

A fir stump, 21" dia., bears S.79½°E., 31.6 ft., no marks visible.

and a new bearing tree

A fir, 18" dia., bears S.33°E., 6.9 ft., mkd. ¼ S30 BT. Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. angle iron driven alongside each corner.