

PRIMARY CORNER DESCRIPTION C C for Secs. 24 & 25 only, (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705, dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 443-44)

Intersect the W. bdy. of Tp. 19 S., R 8 W., at the closing cor. of secs. 24 & 25, established on former survey*, which is a basalt stone 16x10x8 ins., 12" in the ground marked CC on W. face, with 2 notches on S. and 4 notches on N. edges; from which

A Fir 8" dia., bears N.25°W., 30 lks. dist. mkd. T19S R9W S24 BT.

A Fir 7" dia., bears S.37°W., 21 lks. dist. mkd. T19S R9W S25 BT.

(Cor. is 2.23 chs. S. of the ¼ sec. cor. on W. bdy. of sec. 19, T19S R8W)* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM survey by Thomas A. Tillman; Robert L. Holm & Floyd A. Brooks, Cadastral Surveyors, under Group #307, surveyed May 1957/Sept. 1958 - (DCSO records Vol. 31 Page(s) 13020-21)

Point for the closing cor. of secs. 24 & 25, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd: T 19 S T 19 S

CC S 24 S 19
S 25

R 9 W R 8 W
1957

from which

An Alder 10" dia., bears N.76½°W., 57 lks. dist. mkd. T19S R9W S24 CC BT.

An Alder 16" dia., bears S.33½°W., 17 lks. dist. mkd. T19S R9W S25 CC BT.

BLM survey by Donald R. Beck & Peter A. Peterson, Cadastral Surveyors, under Group #307, surveyed April 1968/Aug. 1976 - (DCSO records Vol. 37 Page(s) 15434)

The closing cor., monumented with an iron post 2½" dia., firmly set, projecting 4" above ground, with brass cap mkd. in 1957, from which bearing trees mkd. in 1957:

An Alder snag 16" dia., bears S.33½°W., 17 lks. dist. mkd. T19S R9W S25 CC BT. (Cont. Next Page)

TOWNSHIP 19 RANGE 09 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION C C for Secs. 24 & 25 only, (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

An Alder snag 10" dia., bears N.76½°W., 57 lks. dist. mkd.
T19S R9W S24 CC BT.
and new bearing trees:
An Alder 18" dia., bears S.33°W., 53 lks., mkd. T19S R9W
S25 CC BT.
A Maple 15" dia., bears N.87¼°W., 105 lks. dist. mkd.
T19S R9W S24 CC BT.

Cor. Fd. and tied in BLM resurvey by John P. Farnsworth,
Cadastral Surveyor, under Group #1076, surveyed Sept.
1981/April 1983 - DCSO Records, Vol. 45 Page(s) 17474-75