

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7 only, T19-8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 1 Page(s) 409)

Set post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 6 & 7, mkd. T19S R8W S6 on NE.; T19S R8W S7 on SE. faces, with 1 notch on N. and 5 notches on S. edges; from which

- A Fir 40" dia., bears N.16½°E., 32 lks. dist. mkd. T19S R8W S6 BT.
- A Fir 40" dia., bears S.43½°E., 50 lks. dist. mkd. T19S R8W S7 BT.

BLM survey by Thomas A. Tillman; Robert L. Holm & Floyd A. Brooks, Cadastral Surveyors, under Group #307, surveyed May 1957/Sept. 1958 - (DCSO records Vol. 31 Page(s) 13026-27)

The cor. of secs. 6 & 7 only, determined at record distance from each of the original bearing trees:

- A Fir 52" dia., bears N.40°E., 32 lks. dist., plainly blazed and healed. (Rec. brg. N.16½°E.)
- A Fir 55" dia., bears S.46°E., 50 lks. dist., plainly blazed and healed (Rec. brg. S.43½°E.)

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 19 S		T 19 S
S 12		S 6
		S 7
R 9 W		R 8 W
1957		

Corey Woodruff - For: Plum Cr. Timberland - 5/2009 - M159-30

- Found - 1957 GLO BCIP
- 52" D.Fir bears (N.40°E) is down
- 55" D.Fir bears (S.46°E) is down
- BT mkd - 8" W.Hemlock bears N.2°E., 23.3'
- 13" W.Hemlock bears S.88°E., 46.0'