

PRIMARY CORNER DESCRIPTION SW Tsp. cor. (SW Cor. Sec. 31)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by C.M. Collier, Deputy Surveyor, under Contract 546, dated August 16, 1889 - (DCSO records Vol. 1 Page(s) 104-105)

Set a post 4½ ft. long, 5" sq., 24" in the ground, for cor. of Tps. 19 & 20., Rs. 10 & 11 W., marked T19S S31 on NE.; R10W S6 on SE.; T20S S1 on SW.; and R11W S36 on NW. faces, with 6 notches on each edge; from which

- A Cherry 5" dia., bears N.76°W., 18 lks. dist. mkd. T19S R11W S36 BT.
- A Fir 50" dia., bears S.46½°W., 45 lks. dist. mkd. T20S R11W S1 BT.
- A Fir 36" dia., bears N.77½°E., 29 lks. dist. mkd. T19S R11W S31 BT.
- A Cherry 5" dia., bears S.32½°E., 33 lks. dist. mkd. T20S R10W S6 BT.

Cor. Fd. in GLO survey by Wm. Thiel under Contract #567 dated Feb. 16, 1891 (DCSO records, Vol. 1 Pages 110-111)

Douglas County Surveyors Office - Bruce R. Rogers, Deputy; Mike Stone, crew - June 23, 1965 - C.S. File 53/66-137

Found - 50" Fir now snag, S.46½°W., 29.7 ft.
36" Fir now snag, N.77½°E., 19.1 ft. (See affidavits for evidence of scribing)

Set Brass cap at cor. mkd: Doug. County Surveyors Office
T 19 S
R11W S 36 | S 31 R10W
1965

New BTs -8" Alder S.36°W., 9.4 ft. mkd. T20S R11W S1 CS BT.
12" Alder S.7°W., 16.9 ft. mkd. T20S R11W S1 CS BT.

BLM resurvey by Peter A. Peterson; Glenn F. Goodson; John P. Lee, Cadastral Surveyors, under Group #948, surveyed Aug. 1978/Aug. 1979 - (DCSO records Vol. 41 Page 16297)

The cor. of Tps. 19 S., Rs. 10 and 11 W., perpetuated by Bruce Rogers, in 1965, monumented with an iron post, 1½" dia., firmly set, projecting 12" above ground, with brass cap mkd.: DOUG COUNTY SURVEYORS OFFICE

T 19 S
R S 36 | S 31 R
11 10
W 1965 W

from which the remains of the original bearing trees
(Cont. Next Page)

TOWNSHIP 19 RANGE 10 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW Tsp. cor. (SW cor. Sec. 31)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir snag 32" dia., bears N.77½°E., 29 lks. dist., no marks visible.
A Fir snag 54" dia., bears S.46½°W., 45 lks. dist., with opened blaze, no marks visible.
and bearing trees mkd. by Rogers
An Alder 15" dia., bears S.10 3/4°W., 25 lks. dist., with scribe marks R11W visible on partially healed blaze.
An Alder 12" dia., bears S.36 3/4°W., 14 lks. dist. with scribe marks 20S R11W BT visible on partially healed blaze.
No suitable trees available within limits in secs. 31 and 36.

Fd. OK, Nov. 1984 by D. Peel - M 97-64