TOWNSHIP 19 RANGE 10 POINT IDENTIFIER # 101100

PRIMARY CORNER DESCRIPTION C C Tps. 20 S., Rs. 10 & 11

Alias Description
Alias Description
Alias Description
Alias Description

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 111)

I set a sandstone, 8x8x8 ins., 6" in the ground, for closing cor. to Tps. 20 S., Rs. 10 & 11 W., marked C C with 6 notches on S., E., and W. edges; and raised a mound of stone, 1½ ft. high and 2 ft. base alongside; pits impracticable.

Cor. Fd. and used in GLO surveys by Nathaniel Martin, June 1892 - (DCSO records, Vol. 1 Pages 212 and 253)

Survey by Wilford N. Haines - Nov. 1965 - M 31-6

Set Iron pipe with brass cap mkd: RS 239 C.C. Sec. 1 T20-11W; Sec. 6 T20-10W, from which

14" Fir S.46°E., 34.5 ft., scribed.
30" Fir S.24°W., 65.7 ft., scribed.

BLM Resurvey by Peter A. Peterson; Glenn F. Goodson; John P. Lee, Cadastral Surveyors, under Group #948, surveyed Aug. 1978/Aug. 1979 - (DCSO records Vol. 41 Page(s) 16296-97)

Point for the closing cor. of Tps. 20 S., Rs. 10 and 11 W., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap mkd:

T 19 S R 10 W
S 31
S 1 S 6
R 11 W R 10 W
T 20 S
C C
1979

from which

A Fir 12" dia., bears S.50 3/4°E., 77 lks. dist., mkd. T20S R10W S6 CC BT.
A Fir 38" dia., bears S.42°W., 71 lks. dist., with healed blaze. (mkd. by Wilford N. Haines in 1965, for the cor. he established.)

From this point, a corner established and recorded by Haines, bears N.11°11'W., 0.405 chs. dist., monumented with an iron post, 1½" dia., firmly set, projecting 12" above ground, with brass cap mkd. T20S CC S1 S6 R11W R10W RS239, from which bearing trees mkd. by Haines:

A Fir 18" dia., bears S.46 3/4°E., 54 lks. dist. with healed blaze.
A Fir 38" dia., bears S.23°W., 100 lks. dist. with healed blaze.