

TOWNSHIP 19 RANGE 10 POINT IDENTIFIER # 120100

PRIMARY CORNER DESCRIPTION W. 1/16 cor. bet. Sec. 31; & 6, T20-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Wilford N. Haines, #239 - For: U.S.F.S.; U.S. Plywood and International Paper Co. - Nov. 1965 - M 31-6

Set iron pipe with brass cap mkd: RS 239 S 1/16 S31 T19S R10W S6 T20S R10W, from which new BTs:

24" Fir N.12°E., 23.7 ft.

28" Fir S.76°E., 31.0 ft.

BLM Resurvey by Peter A. Peterson; Glenn F. Goodson; John P. Lee, Cadastral Surveyors, under Group #948, surveyed Aug. 1978/Aug. 1979 - (DCSO records Vol. 41 Page(s) 16296)

(25.265 chs.)

True point for the W 1/16 sec. cor. of sec. 31 only, is located on near vertical exposed bedrock, where it is impracticable to establish a permanent monument.

(25.315 chs.)

Point selected for the witness cor. to the W 1/6 sec. cor. of sec. 31 only.

Set an iron post 28" long, 2½" dia., 24" in the ground with brass cap mkd:

W C
W 1/16 S. 31-
1979

from which

An Alder 15" dia., bears N.89 3/4°E., 103 lks. dist. mkd. X BT.

A Fir 14" dia., bears N.37°W., 112 lks. dist. mkd. X BT.