

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 31; & 6, T20-10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Nathaniel Martin, under Contract 599, dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 212-13)  
 -----  
 Set a sandstone 6x8x10 ins., 6" in ground for ¼ sec. cor. mkd. ¼ S on N. face; and raised a mound of stone 18" high and 2 ft. base, alongside. No timber within limits and pits impracticable.

GLO survey by Nathaniel Martin, under Contract 599, dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 253)  
 -----  
 Top of high ridge, course SW. to ¼ sec.cor., a sandstone, 10x8x4 ins., 4" above ground, which I had previously set for ¼ sec. cor. mkd. ¼ S on N. face by a mound of stone, 18" high, 30" base; pits impracticable.

Wilford N. Haines, #239 - For: U.S.F.S. & U.S. Plywood and International Paper - Nov. 1965 - M 31-6  
 -----  
 Set Iron pipe with brass cap mkd: RS 239 "¼ S31 S6 T19S R10W S6 T20S R10W, from which new BTs:  
     22" Fir, South 4.1 ft., scribed.  
     24" Fir N.15°W., 36.5 ft., scribed.

BLM Resurvey by Peter A. Peterson; Glenn F. Goodson; John P. Lee, Cadastral Surveyors, under Group #948, surveyed Aug. 1978/Aug. 1978 - (DCSO records Vol. 41 Page(s) 16295)  
 -----  
 The ¼ sec. cor. monumented with original unmarked decomposing sandstone 9x8x5 ins., firmly set 4" in the ground and in a scattering mound of stone, 4 ft. base, 6" high. This cor. position is further substantiated by a number of blazed trees located along the W ½ mile bet. secs. 5 and 32, and the E ½ mile bet. secs. 6 and 31, several of which were opened, with overgrowth dating to the time of the original survey. However, no blazed trees were found on a random line extended west from this original corner.  
 At the corner point  
 Set an iron post, 3 ft. long, 2½" dia., 22" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap  
 mkd:           T 19 S R 10 W  
                   S 31  
           ¼    S 6  
                   T 20 S  
                   1979  
 from which

(Cont. Next Page)

TOWNSHIP 19 RANGE 10 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 31; & 6, T20-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 11" dia., bears N.8 3/4°W., 14 lks. dist. mkd. ¼ S31  
BT.

A Fir 11" dia., bears S.14 3/4°E., 20 lks. dist. mkd. ¼ S6  
BT.

Deposit corner stone alongside iron post.

Cor. is located on spur ridge, bears N.10°W. and S.10°E.