

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32; 5 & 6, T20-10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Nathaniel Martin, under Contract 599, dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 213)

-----  
On SE. slope of hill, Set post 4 ft. long, 3½" sq., 24" in the ground, for cor. of secs. 5, 6, 31 and 32, marked T20S Sec. 6 on SW.; R10W Sec. 5 on SE.; Sec. 31 on NW.; Sec. 32 on NE. faces, with 1 notch on W. and 5 on E. edges; from which a  
Maple 4" dia., bears N.68½°E., 50 lks. dist. mkd. T19S R10W Sec. 32 BT.  
Alder 6" dia., bears S.32°W., 75 lks. dist. mkd. T20S R10W Sec. 6 BT.  
Alder 4" dia., bears S.33°E., 25 lks. dist. mkd. T20S R10W Sec. 5 BT.  
No other trees in limits; I raised mound of stone, 18" high, 24" base, around post.  
(See page #253 for re-chaining of this line)

Wilford N. Haines, #239 - For: U.S.F.S.; U.S. Plywood and International Paper Co. - Nov. 1965 - M 31-6

-----  
Set Iron pipe with brass cap mkd: RS 239 T19S R10W S31 S32 S6 S5, from which new BTs:  
40" Fir N.3°W., 27.0 ft.  
14" Fir N.59°E., 21.5 ft.  
30" Fir S.6°E., 25.5 ft.  
40" Fir S.72°W., 59.6 ft.

BLM Resurvey by Peter A. Peterson; Glenn F. Goodson; John P. Lee, Cadastral Surveyors, under Group #948, surveyed Aug. 1978/Aug. 1979 - (DCSO records Vol. 41 Page(s) 16294-5)

-----  
Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 2½ ft. long, 1" dia., 24" in the ground, with brass cap mkd:     T 19 S R 10 W  
                              S 31 S 32  
                              S 6 S 5  
                              T 20 S  
                              1979

from which  
A Fir 16" dia., bears N.34°E., 6 lks. dist. mkd. T19S R10W S32 BT.  
A Fir 19" dia., bears S.1°E., 22 lks. dist. mkd. T20S R10W S5 BT.  
A Fir 26" dia., bears S.55°W., 31 lks. dist. mkd. T20S R10W S6 BT.  
A Fir 13" dia., bears N.24 3/4°W., 30 lks. dist. mkd. T19S R10W S31 BT.  
(Cont. Next Page)

TOWNSHIP 19 RANGE 10 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32; 5 & 6, T20-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

From this point, a corner established and recorded by James W. Prochnau, Eng. #4185, in 1971, bears S.49°06'W., 4.39 chs. dist., monumented with an iron post 2½" dia., firmly set, projecting 15" above ground, with brass cap mkd. SS 1/164 S6 S5 1971 4185, from which bearing trees mkd. by Prochnau:  
A Fir 21" dia., bears S.5°E., 42 lks. dist. with healed blaze.  
A Fir 15" dia., bears N.25°W., 30 lks. dist. with healed blaze.