

TOWNSHIP 19 RANGE 10 POINT IDENTIFIER # 220100

PRIMARY CORNER DESCRIPTION W 1/16 sec. cor. for 32; & 5, T20-10

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Wilford N. Haines, #239 - For: U.S.F.S.; U.S. Plywood and International Paper Co. - Nov. 1965 - M 31-6

Set Iron pipe with brass cap mkd: "RS239 W 1/6 S32 T19S R10W S5 T20S R10W" with scribed new BTs;
40" Fir S.70°W., 19.7 ft.
18" Fir N.5°E., 39.8 ft.

BLM Resurvey by Peter A. Peterson; Glenn F. Goodson; John P. Lee, Cadastral Surveyors, under Group #948, surveyed Aug. 1978/Aug. 1979 - (DCSO records Vol. 41 Page(s) 16293)

Point for the W 1/16 sec. cor. of secs. 5 and 32.
Set an Iron post, 28" long, 2½" dia., 24" in the ground with brass cap mkd:
$$W \frac{1}{16} \frac{S \ 32}{S \ 5}$$
 1979

from which
An Alder 12" dia., bears North, 39 lks. dist., mkd. W 1/16 S32 BT.
A Hemlock 14" dia., bears S.63¼°E., 83 lks. dist. mkd. W 1/16 S5 BT.