

TOWNSHIP 19 RANGE 10 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 300)

The ¼ sec. cor., established on former survey*, which is a post, 3 ft. long, 3" sq., 24" in the ground, mkd: ¼ S29 on N and 32 on S faces; from which

An Alder, 5" dia., bears S.12°E., 16 lks., mkd: ¼ S BT.

A Fir, 10" dia., bears N.60°E., 69 lks., mkd: ¼ S BT.

* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

Donald Peel, LS #752 - For: International Paper Co. - Sept.8, 1982 - M 92-79

Set - USFS 2½" Alum. mon. on a 1½"x36" IP cap mkd: T19S R10W
¼ S29 S32 PLS 742 1982
54" Fir S.3°W., 197.2 ft.
50" Fir S.88½°W., 254.1 ft.