

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33; 4 & 5, T20-10

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Nathaniel Martin, under Contract 599, dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 213-14)

Near foot of hill
Set post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 4, 5, 32 and 33, marked T19S Sec. 33 on NE.; T29S Sec. 4 on SE.; R10W Sec. 5 on SW.; Sec. 32 on NW. faces, with 4 notches on E. and 2 on W. edges; from which an
Alder 6" dia., bears N.5°E., 7 lks. dist. mkd. T19S R10W S33 BT.
Maple 4" dia., bears S.75°E., 15 lks. dist. mkd. T20S R10W S4 BT.
Fir 7" dia., bears S.85°W., 15 lks. dist. mkd. T20S R10W S5 BT.
Fir 8" dia., bears N.65°W., 45 lks. dist. mkd. T19S R10W S32 BT.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated April 8, 1920 - (DCSO records Vol. 1 Page(s) 262)

The sec. cor., which has recently been perpetuated by a Cedar post, 5" sq., 18" above ground, firmly set, mkd. T19S S33 on NE.; R10W S4 on SE.; T20S S5 on SW.; and S32 on NW. face, witnessed by two of the original bearing trees, agreeing with the recorded description, except as to the bearing of the NW. bearing tree. The original NE. bearing tree is found, dead and detached from its original position, marks still decipherable. No trace is found of the original SE. BT.
From the corner.
(New BT) A Fir 30" dia., bears N.35°E., 33 lks. dist. mkd. T19S R10W S33 BT.
(New BT) An Alder 12" dia., bears S.5°E., 42 lks. dist. mkd. T20S R10W S4 BT.
(Old BT) A Fir 20" dia., bears S.85°W., 15 lks. dist., mkd. T20S R10W S5 BT.
(Old BT) A Fir 18" dia., bears N.77°W., 45 lks. dist. mkd. T19S R10W S32 BT.

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #297, Surveyed May 1951/Oct. 1952 - (DCSO records Vol. 27 Page(s) 11682)

The sec. cor., has been remonumented with a steel bolt, 5 ft. long, 3/4" dia., firmly driven 18" in the ground, from which
A Fir 34" dia., bears N.35°E., 33 lks. dist., plainly blazed and healed. (A 1922 bearing tree)
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33; 4 & 5, T20-10

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

An Alder 18" dia., bears S.2½°E., 42 lks. dist., mkd. T20S R10W S4 BT in the bark. (A 1922 BT)

A Fir 34" dia., bears S.85°W., 15 lks. dist. with blaze nearly healed. (An 1892 BT)

A dead Fir 20" dia., bears N.77°W., 46 lks. dist. with blaze partly healed and decayed. (An 1892 BT; rec. dist. 45 lks.)

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 19 S R 10 W
 S 32 S 33
S 5 S 4
T 20 S
1952

from which new bearing trees:

A Fir 26" dia., bears S.20°E., 101 lks. dist. mkd. T20S R10W S4 BT.

A Fir 24" dia., bears N.27°45'W., 109 lks. dist. mkd. T19S R10W S32 BT.

Reset the steel machine bolt alongside the iron post.

(See F.B. 45 Pg. 10 and "Old" renewal Vol. 1 Pg. 16)

BLM Resurvey by Peter A. Peterson; Glenn F. Goodson; John P. Lee, Cadastral Surveyors, under Group #948, surveyed Aug. 1978/Aug. 1979 - (DCSO records Vol. 41 Page(s) 16292)

The sec. cor., monumented with an iron post 2" dia., firmly set, projecting 4" above ground, with brass cap mkd. in 1952, from which the remains of the original bearing tree:

A sawed Fir stump 34" dia., bears S.79°W., 15 lks. dist., with healed blaze. (Rec., S.85°W.)

and the remains of bearing trees mkd. by Mensch:

A decayed Fir stump 34" dia., bears N.29°E., 33 lks. dist., no marks visible. (Rec., N.35°E.)

A decayed Alder stump, size indeterminate, bears S.9°E., 42 lks. dist., no marks visible. (Rec. S.2½°E.)

and a bearing tree mkd. by Tillman:

A Fir 33" dia., bears S.26°E., 101 lks. dist., with healed blaze. (Rec. S.20°E.)

and new bearing trees:

A Fir 24" dia., bears N.40°E., 53 lks. dist. mkd. T19S R10W S33 BT.

A Fir 6" dia., bears N.30°W., 54½ lks. dist. mkd. T19S R10W S32 BT.

No suitable trees available within limits in sec. 5.

(Cont. Next Page)

TOWNSHIP 19 RANGE 10 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33; 4 & 5, T20-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by James W. Prochnau - For: Siuslaw National Forest -
June 30, 1987 - M 104-51 A & B

Found - GLO 2½" brass cap on a 1½" galv. iron pipe set in
1952.

A 24" D.Fir stub, bears S.86°W., 10.7 ft. (Rec.
S.85°W., 15 lks.), healed. (1892 BLM)

A 34" D.Fir bears S.20°E., 66.7 ft. (Rec. S.20°E.,
101 lks.), healed. (BLM 1952)

A 26" D.Fir bears N.40°E., 34.9 ft. (Rec. N.40°E.,
53 lks., healed. (BLM 1979)

A 33" Alder bears N.12°W., 8.6 ft. (Rec. N.16°W.,
8.5 ft.) (1982 RLS 752)

Fd. OK, Dec. 1990 - M 111-33

Fd. OK May 1994 by Mulkins - M 120-13