

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 32, & 33

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 295)

-----  
The cor. of secs. 28, 29, 32, & 33, established on former survey\*, which is a post, 3 ft. long, 4" sq., 24" in ground, marked T19S S28 on NE, R10W S33 on SE, S32 on SW, S29 on NW faces, with 1 notch on S and 4 notches on E edges; from which  
An Alder, 6" dia., bears N.45°E., 39 lks., mkd: T19S R10W S28 BT.  
An Alder, 6" dia., bears S.49°E., 54 lks., mkd: T19S R10W S33 BT.  
An Alder, 6" dia., bears S.41°W., 54 lks., mkd: T19S R10W S32 BT.  
An Alder, 7" dia., bears N.2°W., 32 lks., mkd: T19S R10W S29 BT.

\* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

Donald Peel, Triangle Eng. Co. - For: USFS - Sept. 1980 - M 85-46

-----  
Found - Alder Hub of unknown origin.  
Orig. 21" Alder bears S.46°E., 35.7 ft. with bark scribed.  
Set - USFS 2½" aluminum mon.  
27" Fir bears N.42°E., 80.1 ft.  
52" Fir bears S.86°E., 58.4 ft.  
17" Alder bears S.39°E., 14.3 ft. with bark scribed.  
21" Alder bears N.49°W., 20.7 ft. with bark scribed.  
Note - Position of the alder hub agrees with call note distances to the North Fork Smith River to the West & North but the distance to the East is long.

BLM dependent resurvey by Robert W. Dahl, Cadastral Surveyor, under Group #1450, surveyed Aug. 1988/Oct. 1989 - (DCSO records Vol. 49 Page(s) 18790)

-----  
The Cor. of secs. 28, 29, 32, & 33, perpetuated by Peel in 1980, monumented with an alum. post, 2½" dia., firmly set, projecting 2" above ground, with properly marked alum. cap. from which the remaining orig. BTs:  
An Alder, 22" dia., bears S.45°E., 54 lks., with scribe marks T19S R10W S33 visible on bark. (Rec. S.49°E.)  
(Cont. next page)

TOWNSHIP 19 RANGE 10 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 32, & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

An Alder, 21" dia., bears S.42°W., 54 lks., with old axe marks. (Rec. S.41°W.)  
and the remains of BTs mkd. by Peel  
A Fir, 31" dia. bears N.41°E., 122 lks. with healed blaze.  
A Fir, 55" dia., bears S.87°E., 89 lks. with healed blaze.  
An Alder snag, 20" dia., 50 ft. high, bears S.39°W., 22 lks., with scribe marks T19S R10W S32 BT visible on the bark.  
An Alder, 23" dia., bears N.49°W., 32 lks., with scribe marks T19S R10W S29 BT visible on the bark.  
Corner is located at toe of N. sloping spur.