

TOWNSHIP 19 RANGE 10 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 295)

The ¼ sec. cor., established on former survey, which is a Fir post, 3 ft. long, 3" sq., 24" in the ground, mkd: ¼ S28 on N and 33 on S faces; from which

A Fir, 14" dia., bears N.71°E., 11 lks., mkd: ¼ S BT.

An Alder, 7" dia., bears S.66°E., 67 lks., mkd: ¼ S BT.

* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

Ernesto Alvarado, U.S.F.S., deputized by DCSO -Wit: Carol Dickinson - 10/31/1978 - C.S. File 60/17-18

Found - Orig. 56" D.Fir, bears N.71°E., 7.3 ft. with "S" scribing visible. The face was chopped out by Best & Britton in 11/1961 to find the scribing.

Set - Brass cap mkd: Douglas County Surveyor's Office T19S R10W S28 S33 ¼ 1978

27" D.Fir bears N.82°W., 18 ft., marked double blaze upper ¼ S33 lower CS BT.

Note - Location poster on North shoulder of N. Fork access road which is 600 ft. due South of corner. Corner is located on small spur ridge on North side of N. Fork of Smith River.

Fd. & used on BLM dependent resurvey by Robert W. Dahl, Cadastral Surveyor, under Group #1450, surveyed Aug. 1988/Oct. 1989 - (DCSO records Vol. 49 Page(s) 18789)