

TOWNSHIP 19 RANGE 10 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 297)

-----  
The 1/4 sec. cor., established on former survey\*, which is a post, 3 ft. long, 3" sq., 24" in the ground, mkd: 1/4 S21 on N and 28 on S faces; from which

A Chinquapin, 4" dia., bears N.11°W., 9 lks., mkd: 1/4 S BT.

A Chittem, 5" dia., bears S.6°W., 16 lks., mkd: 1/4 S BT.

\* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM dependent resurvey by Robert W. Dahl, Cadastral Surveyor, under Group #1450, surveyed Aug. 1988/Oct. 1989 - (DCSO records Vol. 49 Page(s) 18793-94)

-----  
Point for 1/4 sec. cor. of secs. 21 & 28, at proportionate distance; there is no remaining evidence of the orig. corner. Set a brass tablet, 3 1/4" dia., 3 1/2" stem, in drill hole in sandstone ledge near base of road cut bank, with top mkd:

T19S R10W  
          S 21  
1/4        S 28  
          1989

from which

A Fir, 8" dia., bears N.49 1/4°E., 51 lks., mkd: 1/4 S21 BT.

A Fir, 8" dia., bears S.62 1/4°W., 308 1/2 lks., mkd: 1/4 S28 BT.