

PRIMARY CORNER DESCRIPTION Cor Secs 27, 28, 33, & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 289)

The cor. to secs. 27, 28, 33, & 34, established on former survey*, which is a Fir tree, 7" dia., mkd: T19S S27 on NE, R10W S34 on SE, S33 on SW, and S28 on NW sides, with 1 notch on S & 3 notches on E sides; from which

- A Fir, 7" dia., bears N.30°E., 18 lks., mkd: T19S R10W S27 BT.
- A Fir, 12" dia., bears S.60°E., 19 lks., mkd: T19S R10W S34 BT.
- A Fir, 12" dia., bears S.51°W., 25 lks., mkd: T19S R10W S33 BT.
- A Fir, 12" dia., bears N.39°W., 16 lks., mkd: T19S R10W S28 BT.

* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - J. Heritage - V. Perron - May 1968 - C.S. File 53/66-39

- Found - Orig. 7", now 16" Fir corner tree, now shattered stump, find scribe & reverse.
- Orig. 7", now 12" snag, N.30°E., 11.9 ft., opened & shows scribe.
 - Orig. 12", now 16" Fir snag, S.60°E., 16.5 ft. (Rec. 12.5 ft) shows scar.
 - Orig. 12", now 30" Fir, S.51°W. 12.5 ft (Rec. 16.5') alive, open to burl wood & rescribe T19S R10W S33 CS BT.
 - Orig. 12", now 17" Fir snag, N.39°W., 10.6 ft., opened to burl.

At a point 1 ft. West of center of corner stump set:

- Set - Brass cap at cor. mkd: COUNTY SURVEYORS T19S R10W OFFICE 1968
- | | | |
|--|-------------|-------------|
| | <u>S 28</u> | <u>S 27</u> |
| | S 33 | S 34 |
- 20" D.Fir N.71°W., 12.0 ft. mkd: T19S R10W S28 CS BT
 - 22" D.Fir S.65°E., 48.5 ft. mkd: T19S R10W S34 CS BT
 - 16" D.Fir N.89°E., 28.9 ft. mkd: T19S R10W S27 CS BT

Note - This corner lies on flat at SW corner of proposed clear cut reported by USFS

Fd. good condition April 1970, T. McCullough - C.S. 55/148-4
Fd. Ok 7/12/1977 - USFS - M 65-63 & C.S. 58/162-2

(Cont. next page)

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias	Description

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - Randy Smith - Nov. 16, 1982 - C.S. File 62/1-29

Found - 1" iron pipe with 1968 County brass cap attached firmly set per 1968 report.
Orig. corner tree, now 16" rotted stub with scribing visible.
IP bears N.58°29'W., 1.3 ft. from center of corner stump. (Rec. per 1968 West 1.0 ft.)

Accessories found from Sec. corner:
Orig. 7" Fir, now 12" snag with scribing visible in previously opened blaze bears N.30°E., 11.9 ft.
Orig. 12", now 38" Fir with good scar S.51°W., 12.5'
Orig. 12", now 20" Fir snag, showing previous axe work bears N.39°W., 10.6 ft.
20 Fir now 23" with good scar bears N.71°W., 12.0 ft. 1968
22" Fir now 37" with good scar bears S.65°E., 47.0 ft. (rec. 48.5 ft) 1968
16" Fir now 18" with good scar bears N.89°E., 27.8 ft. (rec. 28.9 ft) 1968
Set - I add marks "WC to" and S 58 29 E 1.3 ft" to found brass cap.

BLM dependent resurvey by Robert W. Dahl, Cadastral Surveyor, under Group #1450, surveyed Aug. 1988/Oct. 1989 - (DCSO records Vol. 49 Page(s) 18786)

The cor. of secs. 27, 28, 33, & 34, monumented with the orig. corner tree, a rotted Fir snag, 16" dia., 2 ft. high, with fragmentary scribe marks visible on loose piece lying at base, from which the remains of the orig. BTs:
A Fir snag, 12" dia., 5 ft. high, bears N.27°E., 18 lks., with scribe marks T19S R10W S27 visible on opened blaze. (Rec. N.30°E.)
A Fir snag, 16" dia., 20 ft. high, bears S.60°E., 25 lks., with healed blaze. (Rec. 19 lks.)
A Fir, 40" dia., bears S.51°W., 19 lks., with 2 healed blazes. (Rec. 25 lks)
A Fir snag, 17" dia., 10 ft. high bears N.39°W., 16 lks., no marks visible on opened blaze.
and the accessories mkd. by Tracey in 1968:
A Fir, 20" dia., bears N.89°E., 42 lks. with healed blaze.
A Fir, 43" dia., bears S.65°E., 71 lks. with healed blaze.
A Fir, 25" dia., bears N.71°W., 20 lks. with healed blaze.

(Cont. next page)

TOWNSHIP 19 RANGE 10 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

An iron post, 1" dia., firmly set, projecting 6" above ground, bears N.58°29'W., 2.0 lks., with brass cap mkd:
T19S WIT COR S27 S28 S33 S34 S58 29E 1.3 FT R10W 1968

At the corner point
Set an iron post, 28" long, 2½" dia., 23" in the ground, with brass cap mkd:

	T19S R10W
	S 28 S 27
	S 33 S 34
	1988

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.